

The 2EXKL offers a full bodied combo design, with the option of 12W remote capability. Available with Incandescent or LED heads.

## FEATURES

- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC) 1.7 Watts Standard
- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output
- Ceiling or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- White Finish Standard
- Easy Installation
- UL Listed & CEC Registered
- Flame-Retardant, High-Impact, Thermoplastic Housing
- Damp Location
- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Initial Increased LED Brightness Level in Emergency Mode
- (2) 6W Adjustable Lamp Heads or (2) 1W LED Lamp Heads
- 6V Sealed Lead Calcium Battery
- Test Switch
- LED (Power On) Indicator

## WARRANTY

5 Year Warranty

### 2EXKL

#### With Heads on Side

Height: 10.2"  
Width: 21.7"  
Depth: 4.5"

#### With Heads on Top

Height: 15.7"  
Width: 16.3"  
Depth: 4.5"



## 2EXKL

The 2EXKL is available with Red or Green Letters and Incandescent or LED Heads. A Universal stencil is included.

### Options:

- \* **SD** – Self Diagnostic
- \* **RMT** – Remote Capable (Additional 12W per 90 Minutes, also makes it a 4 hour combo if not using additional remote heads)
- \* **LED** – 1W LED Lamp Heads
- \* **BLK** – Black

Lamp Heads on Unit	Series	Universal Faces	Letter Color	Stencil Finish	Housing Finish	Universal	Options
2	EXKL	2	R = Red G = Green	W = White B = Black	W = White B = Black	U	-SD = Self Diagnostics

Green Letter Color, Black Stencil Finish, Black Housing Finish, and Self Diagnostics are available upon Request