

# PTAC Made Simple



## Traditional experience, premium comfort

With **Distinctions** PTAC units, you have a reliable and high-quality option—while your guests enjoy ideal comfort.



| Model                        | DCP<br>073J25BA    | DCP<br>073J35BA    | DCP<br>093J25BA    | DCP<br>093J35BA    | DCP<br>093J50BA    | DCP<br>123J25BA | DCP<br>123J35BA | DCP<br>123J50BA | DCP<br>153J35BA | DCP<br>153J50BA |
|------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Cooling                      |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |
| Voltage                      | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       |
| Capacity (BTU/h)             | 7,300 / 7,200      | 7,300 / 7,200      | 9,200 / 9,000      | 9,200 / 9,000      | 9,200 / 9,000      | 12,000 / 11,800 | 12,000 / 11,800 | 12,000 / 11,800 | 14,700 / 14,500 | 14,700 / 14,500 |
| Amps                         | 3.1 / 3.4          | 3.1 / 3.4          | 4.3 / 4.9          | 4.3 / 4.9          | 4.3 / 4.9          | 5.5 / 6.1       | 5.5 / 6.1       | 5.5 / 6.1       | 7.5 / 8.9       | 7.5 / 8.9       |
| Watts                        | 560 / 550          | 560 / 550          | 790 / 780          | 790 / 780          | 790 / 780          | 1,080 / 1,060   | 1,080 / 1,060   | 1,080 / 1,060   | 1,390 / 1,370   | 1,390 / 1,370   |
| EER                          | 13.1               | 13.1               | 11.3               | 11.3               | 11.3               | 10.7            | 10.7            | 10.7            | 10.6            | 10.6            |
| CFM (cool/wet coil)          | high               | 346                | 346                | 430                | 430                | 430             | 431             | 431             | 431             | 430             |
|                              | low                | 285                | 285                | 342                | 342                | 341             | 348             | 348             | 348             | 349             |
| CFM (dry)                    | high               | 346                | 346                | 430                | 430                | 430             | 431             | 431             | 431             | 430             |
|                              | low                | 285                | 285                | 342                | 342                | 342             | 311             | 348             | 348             | 349             |
| Universal                    |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |
| Vent door CFM                | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 62 / 60 / 56    | 62 / 60 / 56    | 62 / 60 / 56    | 62 / 60 / 56    | 62 / 60 / 56    |
| Dehumidification (pints/hr.) | 0.63               | 0.63               | 1.18               | 1.18               | 1.18               | 2.85            | 2.85            | 2.85            | 4.55            | 4.55            |
| Net weight (lbs.)            | 98.1               | 98.1               | 97.0               | 97.0               | 97.0               | 103.6           | 103.6           | 103.6           | 105.8           | 105.8           |
| Ship weight (lbs.)           | 106.9              | 106.9              | 105.8              | 105.8              | 105.8              | 112.4           | 112.4           | 112.4           | 114.6           | 114.6           |
| Electric Heat                |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |
| Voltage                      | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       |
| Heater size (kW)             | 2.5                | 3.5                | 2.5                | 3.5                | 5                  | 2.5             | 3.5             | 5               | 3.5             | 5               |
| Heating capacity (BTU/h)     | 7,800 / 6,300      | 10,900 / 8,900     | 7,800 / 6,300      | 10,900 / 8,900     | 15,000 / 12,200    | 7,800 / 6,300   | 10,900 / 8,900  | 15,000 / 12,200 | 10,900 / 8,900  | 15,000 / 12,200 |
| Watts                        | 2,580 / 2,150      | 3,500 / 2,897      | 2,580 / 2,150      | 3,500 / 2,897      | 5,000 / 4,100      | 2,580 / 2,150   | 3,500 / 2,897   | 5,000 / 4,100   | 3,500 / 2,897   | 5,000 / 4,100   |
| Amps                         | 11.3 / 10.3        | 15.3 / 13.7        | 11.3 / 10.3        | 15.3 / 13.7        | 22.3 / 20.1        | 11.3 / 10.3     | 15.3 / 13.7     | 22.3 / 20.1     | 15.3 / 13.7     | 22.3 / 20.1     |



| Model                        | DHP<br>073J25BA    | DHP<br>073J35BA    | DHP<br>093J25BA    | DHP<br>093J35BA    | DHP<br>093J50BA    | DHP<br>123J25BA | DHP<br>123J35BA | DHP<br>123J50BA | DHP<br>153J35BA | DHP<br>153J50BA | DHP<br>074J35BA    | DHP<br>094J35BA    | DHP<br>124J35BA | DHP<br>154J35BA |
|------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|-----------------|-----------------|-----------------|-----------------|-----------------|--------------------|--------------------|-----------------|-----------------|
| Cooling                      |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |                    |                    |                 |                 |
| Voltage                      | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       | 265                | 265                | 265             | 265             |
| Capacity (BTU/h)             | 7,200 / 7,100      | 7,200 / 7,100      | 9,300 / 9,200      | 9,300 / 9,200      | 9,300 / 9,200      | 12,000 / 11,800 | 12,000 / 11,800 | 12,000 / 11,800 | 14,700 / 14,500 | 14,700 / 14,500 | 7,200              | 9,000              | 12,000          | 14,700          |
| Amps                         | 3.0 / 3.3          | 3.0 / 3.3          | 4.2 / 4.6          | 4.2 / 4.6          | 4.2 / 4.6          | 5.3 / 5.8       | 5.3 / 5.8       | 5.3 / 5.8       | 6.5 / 7.4       | 6.5 / 7.4       | 2.3                | 3.9                | 5.3             | 5.8             |
| Watts                        | 550 / 540          | 550 / 540          | 820 / 810          | 820 / 810          | 820 / 810          | 1,040 / 1,020   | 1,040 / 1,020   | 1,040 / 1,020   | 1,390 / 1,370   | 1,390 / 1,370   | 605                | 770                | 1,130           | 1,535           |
| EER                          | 13.1               | 13.1               | 11.4               | 11.4               | 11.4               | 10.5            | 10.5            | 10.5            | 10.6            | 10.6            | 11.9               | 11.3               | 10.5            | 9.6             |
| CFM (cool/wet coil)          | high               | 355                | 355                | 363                | 363                | 363             | 438             | 438             | 438             | 416             | 416                | 398                | 389             | 434             |
|                              | low                | 295                | 295                | 300                | 300                | 300             | 344             | 344             | 344             | 330             | 330                | 337                | 328             | 352             |
| CFM (dry)                    | high               | 355                | 355                | 363                | 363                | 363             | 438             | 438             | 438             | 416             | 416                | 398                | 389             | 434             |
|                              | low                | 295                | 295                | 300                | 300                | 300             | 344             | 344             | 344             | 330             | 330                | 337                | 328             | 352             |
| Universal                    |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |                    |                    |                 |                 |
| Vent door CFM                | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 62 / 60 / 56    | 62 / 60 / 56    | 62 / 60 / 56    | 62 / 60 / 56    | 62 / 60 / 56    | 61.1 / 57.6 / 50.6 | 61.1 / 57.6 / 50.6 | 62 / 60 / 56    | 62 / 60 / 56    |
| Dehumidification (pints/hr.) | 0.70               | 0.70               | 1.14               | 1.14               | 1.14               | 2.85            | 2.85            | 2.85            | 4.33            | 4.33            | 0.70               | 1.16               | 3.17            | 4.55            |
| Net weight (lbs.)            | 101.4              | 101.4              | 99.2               | 99.2               | 99.2               | 110.2           | 110.2           | 110.2           | 113.5           | 113.5           | 94.8               | 99.2               | 105.8           | 109.1           |
| Ship weight (lbs.)           | 110.2              | 110.2              | 108.0              | 108.0              | 108.0              | 119.0           | 119.0           | 119.0           | 122.3           | 122.3           | 103.6              | 108.0              | 114.6           | 117.9           |
| Electric Heat                |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |                    |                    |                 |                 |
| Voltage                      | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230          | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       | 208 / 230       | 265                | 265                | 265             | 265             |
| Heater size (kW)             | 2.5                | 3.5                | 2.5                | 3.5                | 5                  | 2.5             | 3.5             | 5               | 3.5             | 5               | 3.5                | 3.5                | 3.5             | 3.5             |
| Heating capacity (BTU/h)     | 7,800 / 6,300      | 10,900 / 8,900     | 7,800 / 6,300      | 10,900 / 8,900     | 15,000 / 12,200    | 7,800 / 6,300   | 10,900 / 8,900  | 15,000 / 12,200 | 10,900 / 8,900  | 15,000 / 12,200 | 10,900             | 10,900             | 10,900          | 10,900          |
| Watts                        | 2,580 / 2,150      | 3,500 / 2,897      | 2,580 / 2,150      | 3,500 / 2,897      | 5,000 / 4,100      | 2,580 / 2,150   | 3,500 / 2,897   | 5,000 / 4,100   | 3,500 / 2,897   | 5,000 / 4,100   | 3,500              | 3,500              | 3,500           | 3,500           |
| Amps                         | 11.3 / 10.3        | 15.3 / 13.7        | 11.3 / 10.3        | 15.3 / 13.7        | 22.3 / 20.1        | 11.3 / 10.3     | 15.3 / 13.7     | 22.3 / 20.1     | 15.3 / 13.7     | 22.3 / 20.1     | 13.2               | 13.2               | 13.2            | 13.2            |
| Reverse Cycle                |                    |                    |                    |                    |                    |                 |                 |                 |                 |                 |                    |                    |                 |                 |
| Capacity (BTU/h)             | 6,200 / 6,000      | 6,200 / 6,000      | 8,100 / 7,900      | 8,100 / 7,900      | 8,100 / 7,900      | 10,800 / 10,500 | 10,800 / 10,500 | 10,800 / 10,500 | 13,500 / 13,200 | 13,500 / 13,200 | 6,000              | 8,000              | 10,800          | 13,300          |
| Amps                         | 2.6 / 2.7          | 2.6 / 2.7          | 3.9 / 4.3          | 3.9 / 4.3          | 3.9 / 4.3          | 5.0 / 5.3       | 5.0 / 5.3       | 5.0 / 5.3       | 6.0 / 6.4       | 6.0 / 6.4       | 2.0                | 2.9                | 5.1             | 5.0             |
| Watts                        | 480 / 460          | 480 / 460          | 720 / 690          | 720 / 690          | 720 / 690          | 890 / 850       | 890 / 850       | 890 / 850       | 1,170 / 1,120   | 1,170 / 1,120   | 620                | 719                | 970             | 1,300           |
| COP                          | 3.6                | 3.6                | 3.40               | 3.40               | 3.40               | 3.2             | 3.2             | 3.2             | 3.2             | 3.2             | 3.3                | 3.3                | 3.2             | 3.0             |
| CFM (dry)                    | 355                | 355                | 363                | 363                | 363                | 438             | 438             | 438             | 416             | 416             | 389                | 388                | 434             | 434             |



## Sales, Support and Service You Can Trust

**Five-Year Limited Warranty:** Enjoy one of the most comprehensive warranties in the industry: First Year: parts & labor; Second through fifth years: parts & labor on certain sealed system components; second through fifth years: on certain functional parts only. For complete warranty details, visit [www.distinctions-ptac.com](http://www.distinctions-ptac.com).

**Distinctions PTAC** are stocked and sold from the same warehouse as the **Amana® Brand PTAC** products you have come to love over the years.

## Features

**R-32 Refrigerant:** 68% lower Global Warming Potential (GWP) and can reduce direct emissions from refrigerant by up to 73.6% as compared to R-410A.

**Dual Fan Motors:** Allows precise independent fan speed while providing quiet operation.

**LCDI Power Cord Included:** No need to match power cord type to unit size.

**3-Speed Fan:** Provide precise comfort control to your guests.

**Constant Fan:** Take advantage of each unit's dual options—select continuous fan operation or cycle the fan ON and OFF with the thermostat. Our 7-button design allows guests to select fan.

**Wired Thermostat Compatible:** Wire your PTAC with any standard thermostat for better temperature control.

**Gold Fin Coils:** Providing seacoast protection on all units.

## Advantages

**Energy Efficiencies:** With EERs up to 13.1 and COPs up to 3.6, our unit's high efficiencies may qualify you for many of the rebates offered by electrical power companies.

**Automatic Emergency Heat:** No more "my unit is not heating" complaints during the middle of the night. Heat pump units will automatically switch over to electric resistance heat if the heat pump compressor system fails or if the heating load is greater than the unit capacity.

**Easy Pull-Out Filters:** Our filters are washable and easy to maintain.

**Condensate Dispersion System:** Our condensate dispersion system removes condensate from indoor cooling operation by throwing water directly on to the outdoor coil for rapid evaporation and increased cooling efficiencies.

**Call your Distinctions Brand PTAC sales representative at 800.647.2982 for complete details.**

Before purchasing this appliance, read important information available from your retailer about its estimated annual energy consumption, yearly operating cost or energy efficiency rating.

Amana® is a registered trademark of Maytag Corporation or its related companies and is used under license. All rights reserved.



Our continuing commitment to quality products may mean a change in specifications without notice.  
©2025 Daikin Comfort Technologies Manufacturing L.P. • Houston, Texas • Printed in the USA.

CB-PTAC-DIST 10-25